



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : H04B 7/195, 7/19	A2	(11) International Publication Number: WO 95/35602 (43) International Publication Date: 28 December 1995 (28.12.95)
---	----	--

(21) International Application Number: PCT/US95/07837

(22) International Filing Date: 21 June 1995 (21.06.95)

(30) Priority Data:  
08/263,835 22 June 1994 (22.06.94) US(71) Applicant: ERICSSON INC. [US/US]; One Triangle Drive,  
P.O. Box 13969, Research Triangle Park, NC 27709 (US).(72) Inventor: DENT, Paul, W.; Stehags Prästgård, S-240 36  
Stehags (SE).(74) Agents: GRUDZIECKI, Ronald, L. et al.; Burns, Doane,  
Swecker & Mathis, P.O. Box 1404, Alexandria, VA 22313-  
1404 (US).(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH,  
CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE,  
KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN,  
MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,  
TJ, TM, TT, UA, UG, UZ, VN, European patent (AT, BE,  
CH, DE, DK, ES, FR, GB, GR, IB, IT, LU, MC, NL, PT,  
SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML,  
MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ,  
UG).


## Published

Without international search report and to be republished  
upon receipt of that report.

(54) Title: RADIOCOMMUNICATION SYSTEM USING GEOSTATIONARY AND NON-GEOSTATIONARY SATELLITES

## (57) Abstract

A radiocommunication system and method using a combination of a geostationary (GEO) and a plurality of medium earth orbit (MEO) satellites are disclosed. First, a GEO satellite is launched to provide initial system capacity. Next, MEO satellites are successively launched into positions where they can supplement the coverage of the GEO satellite during peak traffic hours. Finally, when a sufficient number of MEO satellites are in place, the GEO satellite can provide the supplementary capacity.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

## RADIOCOMMUNICATION SYSTEM USING GEOSTATIONARY AND NON-GEOSTATIONARY SATELLITES

### BACKGROUND

5           The present invention generally relates to methods and systems for providing radiocommunications and, more particularly, to such methods and systems which use satellites to provide radiocommunications.

          In the past, satellite systems for providing global coverage have been of one of three types, broadly classifiable by orbiting distance into geostationary (GEO), low earth orbit (LEO) and medium earth orbit (MEO). An example of a  
10       geostationary satellite communications system is the INMARSAT system (International Maritime Satellite Organization). One advantage of geostationary satellites is that they remain in a fixed position relative to the earth, and only four such satellites are required to illuminate the entire earth. A disadvantage of  
15       geostationary satellites is that they are very distant, needing high transmit power and large antennas to provide communications capacity and incurring about a 1/4 second, round-trip, signal propagation delay.

          An example of a LEO system is the IRIDIUM system proposed by Motorola. An advantage of LEO systems is that the satellites are much closer to  
20       the earth, thereby providing improved communications. Since the satellites are closer to the earth, less transmitting power is needed for both the satellite and an individual user's transceiver. A disadvantage is that about 70 satellites are required to give 24 hour coverage to most points on the globe. Moreover, satellites in low earth orbits move quite rapidly relative to the earth, thereby  
25       causing high Doppler shifts and frequent handovers of communication from one satellite to the next.

          An example of the compromise MEO system is the ODYSSEY satellite system proposed by TRW. The orbital altitude of MEO satellites lies between the GEO and MEO orbits, providing better communication quality than a GEO  
30       system, with less movement and Doppler shift than an LEO system. Moreover, MEO systems provide more or less 24 hour coverage to most points on the globe

using between 8 and 18 satellites which is much less expensive than the about 70 satellite LEO solution.

While the MEO solution represents a good compromise between conflicting requirements, it suffers from a practical disadvantage that almost all satellites must be in place before coverage is sufficient (in percentage of time available) to be considered attractive to subscribers. This lesson was learned from the GPS satellite navigation system, which is also a MEO solution. Thus, a considerable investment spanning a multi-year program is needed before significant revenue can be expected when implementing a MEO system.

Accordingly, it would be desirable to provide radiocommunication systems and methods which overcome the foregoing drawbacks of conventional LEO, MEO and GEO solutions.

### SUMMARY

According to exemplary embodiments of the present invention a hybrid GEO/MEO solution begins life with the launch of a geostationary satellite that provides radiocommunication coverage to a region of major expected traffic growth, but has a limited capacity which is sufficient to support only an initial number of subscribers. This is followed by the successive launch of a number of MEO satellites. The MEO satellites can, initially, supplement the coverage of the geostationary satellite. Later, once sufficient MEO satellites are in orbit, the primary traffic burden can be relegated to the MEO satellites, with the GEO satellite performing a supplementary role. Finally, if desired, enough MEO satellites can be launched to provide all of the desired system capacity.

In this way, a major drawback of MEO systems, specifically the lengthy period between initial launching and sufficient capacity to reach profitability, is overcome since systems according to the present invention provide instant capacity by first launching a geostationary satellite.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

The foregoing, and other, objects, features and advantages of the present invention will be more readily understood upon reading the following detailed description in conjunction with the drawings in which:

5        Figure 1 illustrates a geostationary satellite orbiting the earth according to the present invention;

      Figure 2 illustrates a geostationary satellite and several medium earth orbit satellites according to another exemplary embodiment of the present invention; and

10       Figure 3 shows a geostationary satellite and many medium earth orbit satellites according to an exemplary embodiment.

### **DETAILED DESCRIPTION**

      According to the present invention, Figure 1 shows a first satellite 10  
15       which will be established in a geostationary orbit to provide the initial capacity of the system. Although limited in its capacity, this geostationary satellite 10 can provide sufficient capacity to serve a limited number of subscribers within a predefined geographical coverage or traffic area 20. Thus, for example, if a  
20       terminal unit 30 remains within the geographical coverage area 20 and is one of the limited number of subscribers served by geostationary satellite 10, the terminal unit 30 would expect to receive good service except, perhaps, at peak usage times.

      During a second phase of system development, successive satellites 40 can be launched into a medium earth orbit as seen in Figure 2. For example, such  
25       an orbit could be a so-called harmonically synchronous orbit whereby the satellite orbits the earth an integral number of times in one sidereal day such that the ground track repeats. For example, an orbital radius of 16756 km (orbital height 10386 km) gives 4 orbits per sidereal day. Note that each of the medium earth orbit satellites 40 could have greater nominal capacity than the geostationary  
30       satellite 10 due to their relative proximity. Of course, a single medium earth

orbit satellite 40 will not cover any region on the earth for more than a fraction of a day, for example, for two hours once per day, but this coverage can be chosen to occur at a peak traffic period in the day at least one major traffic location, and thus supplement the limited capacity of the GEO satellite allowing  
5 the number of subscribers to be expanded.

One desirable characteristic of exemplary embodiments according to the present invention is that the modulation and multiple access method (e.g., FDMA, TDMA, CDMA or hybrid thereof) used for two-way exchange of radio signals between a terminal unit and the satellites be the same regardless of  
10 whether the geostationary or medium earth orbit satellites are accessed. It is also desirable that the MEO satellite orbital period be a submultiple of a day such that it repeatedly overflies the chosen service area at the designated peak traffic period.

As more MEO satellites 40 are launched, more and more of the global  
15 traffic from a continuously expanding subscriber base will be taken by the MEO satellites. Ultimately, if enough MEO satellites are launched, the GEO satellite 10 can be dispensed with. However, the number of MEO satellites 40 required to provide coverage 100% of the time at 100% of locations is significantly greater than if these percentages are relaxed, particularly when secondary criteria  
20 are added, such as a mobile-satellite angle of elevation greater than 20 degrees, or visibility of two satellites from every mobile phone for at least 90% of the time, to provide diversity reception.

When a greater number of MEO satellites have been launched, as shown in Figure 3, there will still be "holes" in the coverage where the secondary  
25 criteria are not met at particular locations for some of the time. According to the present invention, the geostationary satellite or satellites are maintained in operation in this phase in order to fill in the holes, thus allowing the secondary criteria to be met with a smaller final number of MEO satellites 40.

It can be seen that the originally launched geostationary satellite 10 has a  
30 different role in three different program phases:

PHASE 1: The geostationary satellite alone provides service to a limited initial subscriber base.

PHASE 2: The geostationary satellite has its capacity supplemented at peak traffic periods by one or more MEO satellites.

5 PHASE 3: The geostationary satellite "fills in" for the holes in the coverage provided by a limited constellation of MEO satellites.

10 In order to operate effectively in all three roles, the geostationary satellite 10 should possess certain characteristics. In particular, to fulfill its phase 3 role, the geostationary satellite should be able to direct capacity to needy regions (e.g., the holes) by means of electronically or mechanically steered antenna beams or switched beams. An exemplary technical solution for directing such capacity would be to use a phased array satellite transponder as disclosed in U.S. Patent Application Serial No. 08/179,953 to Paul W. Dent entitled "A Cellular Satellite  
15 Communications System with Improved Frequency Reuse" filed on January 11, 1994 which disclosure is incorporated, in its entirety, here by reference. An alternative arrangement, however, is the multi-beam parabolic antenna system driven by a so-called matrix power amplifier, as used on current INMARSAT-III satellites, and described in U.S. Patent 3,917,998 to Welti which disclosure is  
20 also incorporated here by reference. The matrix power amplifier arrangement allowing either the power of each transmit amplifier to drive an associated beam, or, with great flexibility, and on a signal-by-signal basis, the power of several power amplifier stages to be collected into a single beam, if that is where the capacity is currently most needed.

25 Although the present invention has been described in terms of the foregoing exemplary embodiments, these embodiments are intended to be illustrative in all respects rather than restrictive of the present invention. For example, although the foregoing exemplary embodiments have only one geostationary satellite and a plurality of medium earth orbit satellites, two or  
30 more geostationary satellites could be provided. Moreover, although it would be

desirable to launch the geostationary satellite first to provide instant capacity, one or more medium earth orbit satellites could be launched before the geostationary satellite. Those skilled in the art will readily appreciate that many modifications and adaptations are contemplated by the present invention whose scope is defined  
5 by the appended claims including all equivalents thereof.

## Claims:

1. A satellite communications system comprising:  
at least one geostationary satellite and at least one medium earth orbiting  
5 satellite for providing radio communications to a plurality of remote subscriber  
terminals, in which the at least one geostationary satellite provides radio  
communications to said remote subscriber terminals during periods when the  
remote subscriber terminals cannot access one of said at least one medium earth  
orbit satellites.  
10
2. A satellite communications system comprising:  
a geostationary satellite which provides radio communication service to a  
plurality of remote subscriber terminals until a first medium orbit satellite is  
operational, wherein said first medium orbit satellite supplements the radio  
15 communication service of said geostationary satellite after the first medium orbit  
satellite is operational.
3. A system according to claim 2 wherein said first medium orbit  
satellite is disposed in a position to cover at least one peak traffic area at peak  
20 times of day.
4. A system according to claim 2 further comprising:  
a plurality of additional medium earth orbit satellites which  
become operational after said first medium orbit satellite becomes operational,  
25 wherein said  
geostationary satellite directs its capacity to serve areas determined based on  
traffic and service capacity of the medium earth orbit satellites.
5. A system according to claim 1 in which said geostationary satellite  
30 is followed successively by an increasing number of medium earth orbit

satellites, said geostationary satellite providing one of: stand alone service to subscribers,  
service to subscribers supplemented at peak periods by at least one medium earth orbit satellite, and service for gaps in coverage provided by said medium earth  
5 orbit satellites.

6. The system according to claim 5, wherein the service provided by said geostationary satellite is determined based on a number of medium earth orbit satellites in orbit.

10

7. A method of providing radiocommunication to a plurality of terminal units comprising the steps of:  
launching a satellite into a geostationary orbit;  
providing radiocommunication service to said plurality of terminal units  
15 using only said geostationary satellite prior to launching additional satellites;  
launching a plurality of satellites into a medium earth orbit; and  
providing radiocommunication service using both said geostationary satellite and at least one of said plurality of medium earth orbit satellites.

20 8. The method of claim 7 wherein said second providing step further comprises the steps of:

providing radiocommunication service using said at least one of said plurality medium earth orbit satellites to supplement said service of said geostationary satellite until a predetermined number of said medium earth orbit  
25 satellites have been launched, after which providing radiocommunication service using said geostationary satellite to supplement service of said medium earth orbit satellites.

9. A satellite communications system for serving a number of  
30 ground-base terminals with varying activity levels comprising:

a geostationary satellite disposed so as to be visible from the service area  
24 hours a day;

at least one sub-synchronous satellite in an orbit having a repeating  
ground track timed to cover said service area at times of expected peak activity  
5 of said ground-based terminals.

10. The communications system of claim 9 further comprising a  
central ground station in communication with said geostationary satellite and with  
said sub-synchronous satellite when visible for relaying signals between the  
10 public switches' telephone and said terminals via at least one of said satellites.

11. The communications system of claim 10 further comprising control  
means to steer antenna spot beams of said geostationary satellite to locations  
momentarily not adequately served by said at least one sub-synchronous satellite.  
15

12. The communications system of claim 11 in which said control  
means is a beamforming computer.

13. The communications system of claim 12 in which said  
20 beamforming computer is located at said central station.

14. A communications system for providing telephone communications  
between portable wireless terminals and the public switched telephone system via  
orbiting satellites comprising:

25 at least one geostationary relay satellite comprising an electronically  
steerable antenna;

at least one sub-synchronous relay satellite;



a tracking network for tracking the instantaneous position of said satellite  
and feeding information to communications gateway stations;

at least one communications gateway station connected to the PSTN and in communication with said at least one geostationary relay satellite, said gateway station comprising:

- control means for controlling the areas illuminated by said
- 5 steerable antenna's beams;
- routing means for routing signals between said portable terminals and the PSTN via a satellite and antenna beam controlled based on information from said tracking network.


1 / 2

*Fig. 1*



*Fig. 2*

2/2

*Fig. 3*